

KATO



FULLY HYDRAULIC EXCAVATORS

REGZM

6 series

PRODUCT LINEUP

<http://www.kato-works.co.jp>

NOTE : Illustrations may include optional equipment. KATO products and specifications are subject to improvements and changes without notice.

● Contact for enquiry:



Obtained authentication of International Specification ISO9001 for quality assurance.

KATO

QUALITY & EXPERIENCE
SINCE 1895

KATO WORKS CO.,LTD.

9-37, Higashi-ohi 1-chome, Shinagawa-ku, Tokyo 140-0011, Japan.
Tel. : Head Office Tokyo(03)3458-1111
Overseas Marketing Department Tokyo(03)3458-1115
Fax. : Tokyo(03)3458-1163

Progress to the Next Stage

KATO WORKS CO.,LTD.

Powerful design structure

- Environmentally friendly
- World level working performance
- Comfortable carrier systems



STANDARD MODEL

HD820-6

Bucket capacity : 0.45m³- 1.10m³(ISO)
 Engine output : 112.5kW / 2,000min⁻¹
 (ISO Net)
 Operating weight : 20,200kg (HD820-6)
 20,700kg (HD820LC-6)
 LWH(Standard) : 9,450×2,820×2,960 (mm)

HD512-6

Bucket capacity : 0.25m³- 0.60m³(ISO)
 Engine output : 75.0kW / 2,000min⁻¹
 (ISO Net)
 Operating weight : 12,500kg (HD512-6)
 12,900kg (HD512LC-6)
 LWH(Standard) : 7,650×2,490×2,800 (mm)

COMPACT TAIL SWING MODEL

HD823_{MR}-6

Bucket capacity : 0.45m³- 1.10m³(ISO)
 Engine output : 112.5kW / 2,000min⁻¹
 (ISO Net)
 Operating weight : 22,400kg (HD823MR-6)
 23,100kg (HD823MRLC-6)
 LWH(Standard) : 8,830×2,820×2,960 (mm)

HD513_{MR}-6

Bucket capacity : 0.25m³- 0.60m³(ISO)
 Engine output : 75.0kW / 2,000min⁻¹
 (ISO Net)
 Operating weight : 13,700kg (HD513MR-6)
 14,100kg (HD513MRLC-6)
 LWH(Standard) : 7,460×2,490×2,800 (mm)

HD308us-6

Bucket capacity : 0.12m³- 0.34m³(ISO)
 Engine output : 40.0kW / 2,000min⁻¹
 (ISO Net)
 Operating weight : 7,300kg (HD308US-6)
 7,800kg (DOZER)
 LWH(Standard) : 5,820×2,300×2,600 (mm)

Dozer Specification
(Optional)